



**ACCEPTED E.P.D.M. MEMBRANE SYSTEMS**  
Meeting CGSB 37-GP-52M & ASTM D 4637

Ethylene Propylene Diene Monomer (EPDM) membranes are categorized as thermoset membranes. Seams are solvent welded in combination with tapes. Adhesives and primers must be supplied by same manufacturer. EPDM is not accepted in Protected Membrane Designs (Inverted Roof Membrane Systems)

1. **Carlisle Sure-Seal** (non-reinforced)  
45mil, 60mil, 90 mil
  - a. Fully adhered
  - b. Loose-laid ballasted
  - c. Mechanically fastened
  
2. **Carlisle Sure-White** (non-reinforced)  
60mil, 90 mil
  - a. Fully Adhered
  
3. **Carlisle Sure-Tough** (reinforced)  
45mil, 60mil, 75mil
  - a. Fully adhered
  - b. Loose-laid ballasted
  - c. Mechanically fastened
  
4. **Firestone RubberGARD** (non-reinforced)  
45mil, 60mil, 90 mil
  - a. Fully Adhered
  - b. Loose-laid ballasted
  - c. Mechanically fastened
  
5. **Firestone ECOWhite** (non-reinforced)  
60mil, 90mil
  - a. Fully Adhered
  
6. **Firestone RubberGARD Max** (Reinforced)  
45mil, 60mil, 75mil
  - a. Fully Adhered
  - b. Loose-laid ballasted
  - c. Mechanically fastened
  
7. **Mule Hide**  
45mil, 60mil, 90mil
  - a. Fully Adhered
  - b. Loose-Laid and Ballasted
  - c. Mechanically Fastened