



ACCEPTED S.B.S. MODIFIED BITUMINOUS MEMBRANE FLASHING

MB 7.2.7.

To qualify for an ARCA 15 Year Warranty Certificate, base ply membrane flashing materials shall be polyester or composite reinforced with a minimum thickness of 3.0mm (118 mils) conforming to ASTM D6162 or ASTM D6164.

MB 7.2.8.

To qualify for an ARCA 15 Year Warranty Certificate, cap ply membrane flashing materials shall be polyester or composite reinforced with a minimum thickness of 4.0mm (157 mils) conforming to ASTM D6162 or ASTM D6164.

IKO

15 Year ARCA Warranty IKO	BASE PLY	CAP PLY
	Armourbond 180 (SA) Torchflex TP-180 Torchflex HD-FF Fast-N-Stick 180 Base Protectobase 180	Torchflex TP-250 Cap Prevent TP-250 Cap Torchflex TP-250 Cap 5.0 Prevent TP-250 Cap 5.0 Prevent Premium TP-250 Cap 5.0 Torchflex TP-HD-Cap

SOPREMA

15 Year ARCA Warranty SOPREMA	BASE PLY	CAP PLY
	Soprasmart Board 180 Sopralene Flam 180 Sopralene Stick HR 20 (SA) Soprafix 630 Sopraply 520	Sopralene Flam 250 GR Sopralene Flam 250 FR Soprafix Traffic Cap 660 Sopraply Traffic Cap FR 661 Sopraply Traffic Cap 560

SIPLAST

15 Year ARCA Warranty SIPLAST	BASE PLY	CAP PLY
	Paradiene 20 Paradiene 20 TG Paradiene 20 EG T Paradiene 20 HT TG	Parafor 30 TG Parafor 50 TG