

## ACCEPTED THERMOPLASTIC MEMBRANE SYSTEMS

Minimum thickness of PVC membranes is 48 mil (1.2 mm). Thicker sheets are also available and accepted by ARCA Warranty Ltd. Membrane seams are sealed by hot-air welding with specialized equipment.

### Polyvinyl Chloride (P.V.C.) Membrane Meeting CGSB-37-GP-54M standards

<b>Carlisle PVC Membranes</b>	<b>Attachment Method</b>				<b>ARCA Warranty Certificate</b>		
	<i>Fully Adhered</i>	<i>Loose-Laid Ballasted</i>	<i>Mech. Fast.</i>	<i>Rhinobond (Induction Welded)</i>	<i>5 Year</i>	<i>10 Year</i>	<i>15 Year</i>
Sure-Flex 50 mil	●	●	●		●	●	
Sure-Flex 60 mil	●	●	●	●	●	●	
Sure-Flex 80 mil	●	●	●	●	●	●	●
Approved Adhesives:	Sure-Flex PVC Bonding Adhesive Low VOC PVC Bonding Adhesive Hydrobond Water-Based Adhesive Aqua Base 120 Bonding Adhesive						

<b>Sika-Sarnafil PVC Membranes</b>	<b>Attachment Method</b>					<b>ARCA Warranty Certificate</b>		
	<i>Fully Adhered</i>	<i>Loose-Laid Ballasted</i>	<i>Mech. Fast.</i>	<i>Rhinobond (Induction Welded)</i>	<i>Protected Membrane</i>	<i>5 Year</i>	<i>10 Year</i>	<i>15 Year</i>
Polyester reinforced 60 mil	●	●	●	●	●	●	●	
Polyester reinforced 72 mil	●	●	●	●	●	●	●	
Polyester reinforced 80 mil	●	●	●	●	●	●	●	●
	*Fully Adhered includes Décor Batten & Profile Systems							
Approved Adhesives:	Sarnacol-2170R Adhesive Sarnacol-2121 Adhesive Sarnacol-2170 VC Adhesive							