

ACCEPTED S.B.S. MODIFIED BITUMINOUS MEMBRANE FLASHING

Styrene butadiene styrene (SBS) membranes are categorized as modified bituminous (MB) membranes. Modified bituminous membranes shall comply with the requirements of CGSB 37-GP-56M / CSA A123.23-15. All modified bituminous membrane flashing components shall be from the same manufacturer.

IKO Membrane Flashing Base Sheet	Attachment Method					Surfaces (Bottom/Top)			ARCA Warranty Certificate		
	Adhered (adhesive)	Adhered (asphalt)	Self Adhered	Mech. Fast.	Torch	S=Sanded Surface SA=Self-Adhered TF=Thermofusible Film RF=Release Film O=Other	5 Year	10 Year	15 Year		
Armourbond Flash Sand			•			SA / S	•	•			
Armourbond Flash			•			SA / TF	•	•			
Armourbond Flash HD			•			SA / TF	•	•			
Armourbond 180			•			SA / TF	•	•			
ArmourStick HD-Base			•			SA / RF	•	•			
Fast-N-Stick 180 Base				•		S / TF	•	•			
Modflex MP-180	•	•				S / TF	•	•			
Torchflex TF-95					•	TF / S	•	•			
Torchflex TP-180					•	TF / TF	•	•			
Protectobase	•	•				O / TF	•	•			
Protectobase 180	•	•		•		O / TF	•	•			
ShieldBase 180	•	•		•		O / TF	•	•			
ShieldBase 180 Sanded	•	•		•		S / TF	•	•			
Approved Adhesives: IKO Millenium Adhesive (Protectobase, Protectobase 180, ShieldBase 180 & ShieldBase 180 Sanded ONLY) IKO Cold Gold Flashing Adhesive											

IKO Membrane Flashing Cap Sheet	Attachment Method				Surfaces (Bottom/Top)			ARCA Warranty Certificate		
	Adhered (adhesive)	Adhered (asphalt)	Self Adhered	Torch	S=Sanded Surface SA=Self-Adhered TF=Thermofusible Film GR=Granules O=Other	5 Year	10 Year	15 Year		
ArmourStick HD-Cap			•		SA / GR	•	•			
Modflex MP-180-Cap	•				S / GR	•	•			
Prevent TP-250 Cap				•	TF / GR	•	•			
Prevent TP-250 Cap 5.0				•	TF / GR	•	•			
Prevent TP-HD-Cap				•	TF / GR	•	•			
Torchflex TP-180 Cap				•	TF / GR	•	•			
Torchflex TP-250 Cap				•	TF / GR	•	•			
Torchflex TP-250 Cap 5.0				•	TF / GR	•	•			
Torchflex TP-HD-Cap				•	TF / GR	•	•			
Approved Adhesives: IKO Cold Gold Flashing Adhesive										

Polyglass Base Sheet Membranes	Attachment Method					Surfaces (Bottom/Top)			ARCA Warranty Certificate		
	Adhered (adhesive)	Adhered (asphalt)	Self Adhered	Mech. Fast.	Torch	S=Sanded Surface SA=Self-Adhered TF=Thermofusible Film O=Other	5 Year	10 Year	15 Year		
Elastoflex S6	•	•		•	•	S / TF	•	•			
Elastoflex S6 22	•	•		•	•	S / TF	•	•			
Elastoflex SA Base			•			SA / TF	•	•			
Elastoflex VP					•	TF / TF	•	•			
Elastoflex SA Base Plus			•			SA / TF	•	•			
Elastoflex SA Base Polar			•			SA / TF	•	•			
Approved Adhesives:											

Polyglass Cap Sheet Membranes	Attachment Method				Surfaces (Bottom/Top) S=Sanded Surface SA=Self-Adhered TF=Thermofusible Film GR=Granules O=Other	ARCA Warranty Certificate		
	Adhered (adhesive)	Adhered (asphalt)	Self Adhered	Torch		5 Year	10 Year	15 Year
Elastoflex S6 G				•	TF / GR	•	•	
Elastoflex S6 G HP				•	TF / GR	•	•	
Elastoflex VP G HP				•	TF / GR	•	•	
Elastoflex SA P			•		SA / GR	•	•	
Elastoflex SA P Polar			•		SA / GR	•	•	

Approved Adhesives:

Soprema Membrane Flashing Base Sheet	Attachment Method					Surfaces (Bottom/Top) S=Sanded Surface SA=Self-Adhered TF=Thermofusible Film O=Other	ARCA Warranty Certificate		
	Adhered (adhesive)	Adhered (asphalt)	Self Adhered	Mech. Fast.	Torch		5 Year	10 Year	15 Year
Colply Base 410	•	•				S / S	•	•	
Colvent Base 830			•			SA / TF	•	•	
Colvent Base 840			•			SA / S	•	•	
Elastophene 180 PS		•				S / TF	•	•	
Sopraply Flam Stick			•			SA / S	•	•	•
Sopraply Stick Duo			•			SA / S	•	•	•
Sopraflash Stick			•			SA / S	•	•	
Sopraflash Stick Duo			•			SA / S	•	•	
Sopraflash Flam Stick			•			SA / S	•	•	
Soprafix Base 630				•		S / TF	•	•	•
Sopralene Flam 180					•	TF / TF	•	•	
Sopraply Base 510		•				S / TF	•	•	
Sopraply Base 520					•	TF / TF	•	•	•
2-1 Soprasmart FB	•	•		•		O / TF	•	•	
2-1 Soprasmart Board	•	•		•		O / TF	•	•	•
2-1 Soprasmart Board Sanded	•	•		•		O / S	•	•	•
2-1 Soprasmart ISO HD	•	•		•		O / TF	•	•	•
2-1 Soprasmart ISO HD Sanded	•	•		•		O / S	•	•	•
2-1 Soprasmart Rock		•		•		O / TF	•	•	

Approved Adhesives:

Soprema Duotack Adhesive (2-1 Soprasmart FB, 2-1 Soprasmart Board / Sanded & 2-1 Soprasmart ISO HD / Sanded ONLY)
Soprema Duotack 365 Adhesive (2-1 Soprasmart FB, 2-1 Soprasmart Board / Sanded & 2-1 Soprasmart ISO HD / Sanded ONLY)

Soprema Membrane Flashing Cap Sheet	Attachment Method				Surfaces (Bottom/Top) S=Sanded Surface SA=Self-Adhered TF=Thermofusible Film GR=Granules O=Other	ARCA Warranty Certificate		
	Adhered (adhesive)	Adhered (asphalt)	Self Adhered	Torch		5 Year	10 Year	15 Year
ColPly Traffic Cap Flex	•			•	S / GR	•	•	
Sopralene Mammouth GR				•	TF / GR	•	•	
Sopralene Flam 180 GR				•	TF / GR	•	•	
Sopralene Flam 180 FR GR				•	TF / GR	•	•	
Sopralene Flam 250 GR				•	TF / GR	•	•	•
Sopralene Flam 250 FR GR				•	TF / GR	•	•	•
Sopraply Stick Traffic Cap			•		SA / GR	•	•	
Sopraply Traffic Cap				•	TF / GR	•	•	•
Sopraply Traffic Cap FR				•	TF / GR	•	•	•

Approved Adhesives:

Soprema Colply Traffic Cap Flex approved with Soprema ColPly EF Flashing Cement ONLY.



2380 Pegasus Road NE
Calgary, AB T2E 8G8
Telephone: (403) 250-7055
Toll Free: 1-800-382-8515
Fax: (403) 250-1702
www.arcaonline.ca

ACCEPTED LIQUID-APPLIED MEMBRANE FLASHINGS - 5 and 10 Year W.C.

IKO

IKO MS Detail – One component (Modified Silicone) with polyester mesh reinforcement fabric

SOPREMA

Alsan – One component (Polyurethane/Bitumen Resin) with Alsan Polyester Fleece reinforcement fabric

Alsan RS 230 – Two component PMMA Acrylic Resin

POLYGLASS

Polyglass Polyflash 1-C

ACCEPTED LIQUID-APPLIED MEMBRANE FLASHINGS – 15 Year W.C.

IKO

Metatech – Two component PMMA Acrylic Resin

SOPREMA

Alsan RS 230 – Two component PMMA Acrylic Resin